

Cable Connectors

MPC connectors are equipped with heat and oil resistant covers, Zinc plated cover and ball-point cable screws. Connectors are interchangeable with older Tweco MBP connectors. The whip cable connector is used when downsizing cable to an electrode holder. It is a No.2 male connector with cable hole sized to fit 4,2,1 or 1/0 cable. The 2-1-MPC will fit any No. 2 or No. 4 female connector.



Part No. 2-MPC

Part No.	Model No.	Description	Type Cable Connection	Cable Capacity	Std. Pkg.
MPC Series Positive-CAM Mechanical Connection - Zinc Plated Type Cable & Cover Screws					
1-MPC	9425-1100	Complete connection	Single ball-point	4, 2, 1	1 ea. male/female
1-MPC-1	9425-1110	Male half	Single ball-point	4, 2, 1	2 ea. male
1-MPC-2	9425-1120	Female half	Single ball-point	4, 2, 1	2 ea. female
2-MPC	9425-1200	Complete connection	Single ball-point	1/0, 2/0, 3/0	1 ea. male/female
2-MPC-1	9425-1210	Male half	Single ball-point	1/0, 2/0, 3/0	2 ea. male
2-MPC-2	9425-1220	Female half	Single ball-point	1/0, 2/0, 3/0	2 ea. female
4-MPC	9425-1400	Complete connection	Double ball-point	3/0 or 4/0	1 ea. male/female
4-MPC-1	9425-1410	Male half	Double ball-point	3/0 or 4/0	2 ea. male
4-MPC-2	9425-1420	Female half	Double ball-point	3/0 or 4/0	2 ea. female
2-1-MPC	9425-1140	Whip connection	Single ball-point	4, 2, 1, 1/0	2 ea.

Ground Clamps

GC-300 Ground Clamp

- 98% copper alloy jaws
- Fully insulated spring

SGC-300 Ground Clamp

- Steel body with direct ground through copper alloy jaw
- SGC-500 w/copper shunt
- SGC-300 s/o copper shunt

FGC-300 Ground Clamp

- 98% copper alloy
- 200, 300 & 500 AMP flat jaw



Part No. GC-300



Part No. SGC-300



Part No. FGC-300

Part No.	Model No.	AMP Capacity	Jaw Opening	Cable Connection Capacity	Length (inches)	Length (mm)
GC-200	9205-1120	200	1" - depth 3"	Ball-point thru 1/0	6"	157
GC-300	9205-1130	300	1-1/2" - depth 4"	Ball-point thru 3/0	8-1/2"	216
GC-500	9205-1150	500	2" - depth 5-1/4"	Ball-point thru 4/0	10"	254
SGC-300	9205-1230	300	2" - depth 1-3/4"	1/2" stud connection	9"	228
SGC-500	9205-1250	500	2" - depth 1-3/4"	1/2" stud connection	9"	228
FGC-200	9205-1320	200	5/8" - depth 2"	Ball-point thru 1/0	5"	127
FGC-300	9205-1330	300	1" - depth 3-1/2"	Ball-point thru 3/0	7-1/4"	184
FGC-500	9205-1350	500	1-1/2" - depth 3-1/4"	Ball-point thru 4/0	9-1/4"	234

TwecoTong Electrode Holders

- Feature reversible top and bottom insulators.
- Efficient 6-position jaw patterns.
- Fully insulated.
- Protected springs.
- Ball-point cable connection.



Part No. A-14-HD

Part No.	Model No.	AMP Capacity	Body Alloy	Electrode Capacity	Cable Connection Capacity	Length (inches)	Length (mm)
A-532	9110-1101	200	Copper	thru 5/32"	Ball-point thru 2/0	8-1/2"	216
A-316	9110-1102	250	Copper	thru 3/16"	Ball-point thru 2/0	9-1/4"	235
A-732	9110-1103	300	Copper	thru 7/32"	Ball-point thru 2/0	10"	254
A-14	9110-1104	350	Copper	thru 1/4"	Ball-point thru 4/0	11"	279
A-14-HD	9110-1105	400	Copper	thru 1/4"	Double ball-point thru 4/0	12"	305
A-38-HD	9110-1106	500	Copper	thru 3/8"	Double ball-point thru 4/0	13-1/4"	336

Part No.	Model No.	Description	AMP Capacity	Electrode Capacity	Cable Connection Capacity	Length (inches)	Length (mm)
9120-1000	04TT	Tweco-Tite® holder	400	1/16" thru 1/4"	thru 3/0	9"	229